

360° PRESENCE DETECTOR WITH DIMMING CONTROL



55-365

Description	Colour	Model
Flush Mount Detector	White	55-365

- Multi-function
  - On/Off
  - 1-10V dimming
  - Time adjustment
  - Light sensing
- Cutout diameter: 66mm
- ABS construction
- Programmed by remote control (55-211 optional accessory)



55-211

TECHNICAL DATA

<b>Mounting</b>	Flush
<b>Sensor Adjustment</b>	Adjustable with Lens Shield
<b>Sensor Type</b>	High Frequency 5.8GHz
<b>Detection Range</b>	8m Diameter at 2.5m High
<b>Detection Angle</b>	360°
<b>Time on Adjustment</b>	10 sec to 30 mins
<b>Lux Setting (Lux)</b>	Adjustable from approx. 10 Lux to 2000 Lux
<b>Load</b>	Incandescent Lamp: max. 2000W AC Halogen Lamp: max. 1000W LV Halogen Lamp: max. 1000VA/600W (traditional) max. 1000VA/900W (electronic) Fluorescent Lamp: max. 1000VA/600W (uncompensated) Electronic Ballast: max. 100mA (50 pieces)
<b>Operating Temperature</b>	0°C to + 45°C
<b>Environmental Protection</b>	IP 40 Detector, IP20 Power Box
<b>Power Consumption</b>	0.5W

