



360° MINI PRESENCE DETECTOR WITH DIMMING CONTROL



Actual Size



55-453



Power Box



Description	Colour	Model
Mini Flush Mount Detector	White	55-453

- Multi-function
 - On/Off
 - 1 to 10V dimming
 - Time adjustment
 - Light sensing
- Cutout diameter: 33mm
- ABS construction
- Programmed by remote control (55-211 optional accessory)

TECHNICAL DATA

Mounting	Flush
Sensor Adjustment	Adjustable with Lens Shield
Sensor Type	High Frequency 5.8GHz
Detection Range	8m Diameter at 2.5m High
Detection Angle	360°
Time on Adjustment	10 sec to 30 mins
Lux Setting (Lux)	10 to 2000
Load	Incandescent Lamp: max. 2000W AC Halogen Lamp: max. 1000W LV Halogen Lamp: max. 1000VA/600W (traditional) max. 1000VA/900W (electronic) Fluorescent Lamp: max. 1000VA/600W (uncompensated) Electronic Ballast: max. 100mA (50 Pieces)
Voltage	230v ± 10% 50 Hz
Operating Temperature	0 °C to + 45 °C
Environmental Protection	IP 40 Detector, IP20 Power Box
Power Consumption	0.5W



55-211

